

Silikon- und andere temperaturbeständige Leitungen

Artikel Kurzzeichen	Dimension n x m	Artikelfarbe	Ø mm	Gewicht kg / km	Kupfer kg / km	Preis € / km
SILIKON UND TEXTILISOLIERTE LEITUNG						
SILIKONADERLEITUNG EINDRÄHTIG						
SiD 0,50			1,8	7,6	5,0	228,20
SiD 0,75			2,0	10,4	7,5	274,20
SiD 1,0			2,1	13,1	10,0	311,10
SiD 1,5			2,6	20,0	15,0	399,60
SiD 2,5			3,2	32,0	25,0	589,30
SiD 4,0			3,7	47,0	40,0	875,60
SILIKONADERLEITUNG FEINDRÄHTIG						
SiF 0,50			2,1	8,6	5,0	315,70
SiF 0,75			2,4	11,0	7,5	373,60
SiF 1,0			2,5	15,3	10,0	414,10
SiF 1,50			2,8	20,0	15,0	485,00
SiF 2,50			3,4	32,0	25,0	691,50
SiF 4,0			4,2	48,0	40,0	1.002,80
SiF 6,0			6,2	77,0	60,0	1.399,00
SiF 10			6,8	124,0	100,0	2.187,50
SiF 16			8,0	188,0	160,0	3.275,60
SiF 25			9,7	292,0	250,0	5.036,60
SiF 35			11,2	400,0	350,0	6.596,20
SiF 50			13,6	561,0	500,0	9.324,20
SiF 70			14,8	766,0	700,0	12.946,40
SiF 95			18,2	1.030,0	950,0	16.297,40
SiF 120			19,5	1.296,0	1.200,0	21.955,00
SiF 150			21,9	1.612,0	1.500,0	28.042,70
SiF 185			24,8	1.974,0	1.850,0	34.067,80
SiF 240			26,7	2.553,0	2.400,0	45.053,80
SILIKONADERLEITUNG HOCHFLEXIBEL						
SiFF 0,25			2,0	6,0	2,5	1.385,70
SiFF 0,50			2,2	8,6	5,0	663,00
SiFF 0,75			2,3	11,0	7,5	784,60
SiFF 1,50			2,9	20,0	15,0	1.437,60
SiFF 2,50/3,0 (90x7x0,07)			3,0	20,0	25,0	1.728,80
XSiFF 3,60/5,4(0,07)			5,4	68,0	36,0	2.988,50
SiFF 4,00			6,0	55,0	40,0	8.204,10
SILIKONADERLEITUNG KERBFEST						
SiFK 0,75			2,4	11,0	7,5	529,60
SILIKON HOCHSPANNUNGSLEITUNG < 7,5 KV						
SIFZü						
SIFZü 1,0 / 3 kV			7,0	35,0	10,0	2.426,10
SIFZü 1,0 / 7 kV			7,0	35,0	10,0	2.426,10
SIFZü 1,5 / 7/10 kV			8,0	50,0	15,0	3.777,10
SIFZü 10 / 6 kV			10,0	130,0	100,0	11.688,50
SILIKONZWILLINGSLEITUNG						
SiFZW 2x0,75			2,4 x 5,4	25,0	15,0	784,60
SiFZW 2x1,0			2,6 x 5,6	30,0	20,0	904,10
SILIKONMANTELLEITUNGEN SIHF						
SiHF-O 2x0,50			6,0	50,0	10,0	1.671,60
SiHF-O 2x0,75			6,4	57,0	15,0	1.795,10
SiHF-O 2x1,0			6,6	64,1	20,0	1.926,80
SiHF-O 2x1,5			8,0	87,2	30,0	2.382,80
SiHF-O 2x2,5			9,5	137,0	50,0	3.468,60
SiHF-O 2x4,0			11,3	191,0	80,0	4.893,20
SiHF-O 2x6,0			13,5	240,0	120,0	6.933,00
SiHF-J 3x0,75			6,8	66,1	22,5	1.992,60
SiHF-J 3x1,0			7,4	81,9	30,0	2.408,60
SiHF-J 3x1,5			8,3	104,1	45,0	2.711,90
SiHF-J 3x2,5			10,0	164,3	75,0	3.979,40
SiHF-J 4x0,75			7,8	67,0	30,0	2.619,90
SiHF-J 4x1,0			8,0	100,9	40,0	2.825,60
SiHF-J 4x1,5			9,0	127,4	60,0	3.243,90
SiHF-J 4x2,5			11,0	200,0	100,0	4.722,60
SiHF-J 4x4,0			13,3	329,0	160,0	7.004,30
SiHF-J 4x6,0			16,3	462,0	240,0	10.058,70
SiHF-J 4x10,0			21,4	709,0	400,0	15.982,70
SiHF-J 4x16			24,0	1.014,0	640,0	23.077,30
SiHF-J 4x25			27,5	1.557,0	1.000,0	31.942,80
SiHF-J 5x0,75			8,5	105,2	37,5	3.062,60
SiHF-J 5x1,0			8,8	121,0	50,0	3.362,10
SiHF-J 5x1,5			9,8	148,4	75,0	3.855,70
SiHF-J 5x2,5			11,9	240,1	125,0	5.734,50

Silikon- und andere temperaturbeständige Leitungen

Artikel Kurzzeichen	Dimension n x m	Artikelfarbe	Ø mm	Gewicht kg / km	Kupfer kg / km	Preis € / km
SiHF-J 5x4,0			15,0	399,0	200,0	8.583,00
SiHF-J 5x6			17,7	547,0	300,0	11.939,70
SiHF-J 7x0,75			9,5	130,0	52,5	3.703,80
SiHF-J 7x1,0			9,8	151,0	70,0	4.129,50
SiHF-J 7x1,5			10,9	198,5	105,0	4.586,20
SiHF-J 7x2,5			13,1	300,0	175,0	7.068,10
SiHF-J 12x1,0			12,5	290,0	120,0	7.981,70
SiHF-J 12x1,5			14,5	353,0	180,0	8.901,70
SiHF-J 24x1,5			21,0	723,0	360,0	15.444,70
SILIKONMANTELTG. GESCHIRMT SIFCuSi SIHFCuSi						
SIFCuSi-J 3x1,0			9,0	160,0	92,0	5.484,90
SIFCuSi-J 3x1,5			10,0	180,0	107,0	6.840,40
SILIKONMANTEL KERBFEST						
SiHFK 2x0,75			6,4	53,4	15,0	3.160,60
SiHFK 3x0,75			6,8	63,7	22,5	3.381,50
SiHFK 4x0,75			7,8	83,6	30,0	4.290,60
SiHFK 5x0,75			8,5	101,2	37,5	5.260,50
SiHFK 2x1,00			6,6	60,0	20,0	3.354,90
SiHFK 3x1,00			7,4	78,2	30,0	4.027,60
SiHFK 4x1,00			8,0	94,5	40,0	4.726,80
SiHFK 5x1,00			8,8	116,0	50,0	5.851,30
SiHFK 7x1,00			9,5	150,0	70,0	7.166,90
SiHFK 2x1,50			8,0	81,7	30,0	4.027,60
SiHFK 3x1,50 EWKF			8,5	98,3	45,0	4.802,60
SiHFK 4x1,50			9,5	122,4	60,0	5.491,20
SiHFK 5x1,50			10,4	148,0	75,0	6.513,50
SiHFK 7x1,50			11,2	187,3	105,0	8.388,70
SiHFK 2x2,50			9,4	135,0	50,0	6.006,40
SiHFK 3x2,50			9,8	152,3	75,0	6.891,20
SiHFK 4x2,50 EWKF			11,1	188,7	100,0	8.194,30
SiHFK 5x2,50			12,4	229,0	125,0	9.915,60
SiHFK 3x4,0			11,4	230,0	120,0	9.773,00
SiHFK 4x4,0			13,1	300,0	160,0	12.021,90
SiHFK 5x4,0			14,4	380,0	200,0	14.684,60
SiHFK 3x6,0			14,2	330,0	180,0	13.820,00
SiHFK 4x6,0			16,2	430,0	240,0	17.052,50
SiHFK 5x6,0			17,7	550,0	300,0	20.228,80
SILIKONKOMBILEITUNG						
SILIKON / PVC-LEITUNGEN SIFY						
SiFY 2x0,75 /1			6,0 (+-0,2)	59,0	15,0	747,70
SiFY 2x0,75 /2			6,0 (+-0,2)	59,0	15,0	747,70
SiFY 2x1,0 / 1			6,8	64,0	20,0	841,20
SiFY 2x1,0 / 2			6,8	64,0	20,0	841,20
SiFY 2x1,0 / 3			6,8	64,0	20,0	841,20
SiFY 2x1,0 / 4			6,8	64,0	20,0	841,20
SiFY 2x1,0 / 6			6,9	64,0	20,0	841,20
SiFY 2x1,0 / 5			6,8	64,0	20,0	841,20
SiFY 2x1,0 / 6			6,8	64,0	20,0	841,20
SiFY 2x1,0 / 7			6,8	64,0	20,0	841,20
SiFY 3x1,0/1			7,4	81,0	30,0	1.273,40
SILIKONGLASSEIDENLEITUNG						
SILIGLASSEIDENADER FEINDRÄHTIG						
Sif-GI 0,50			2,4	12,0	5,0	608,90
Sif-GI 0,75			2,7	15,0	7,5	690,30
Sif-GI 1,00			2,8	18,0	10,0	768,50
Sif-GI 1,50			3,3	26,0	15,0	856,20
Sif-GI 2,50			3,9	38,0	25,0	1.117,60
Sif-GI 4,0			4,5	55,0	40,0	1.543,00
Sif-GI 6,0			5,2	76,0	60,0	2.033,50
Sif-GI 10			7,3	136,0	100,0	3.305,00
Sif-GI 16			8,3	200,0	160,0	4.734,70
Sif-GI 25			10,2	311,0	250,0	6.870,50
Sif-GI 35			11,4	412,0	350,0	8.855,10
GLASSEIDENADER FEINDRÄHTIG						
GLTR 1,5			3,3	26,0	15,0	1.610,80
GLTR 2,5			3,9	38,0	25,0	2.200,60
GLTR 4,0			4,5	55,0	40,0	3.520,90
GLTR 6,0			5,2	76,0	60,0	4.183,90
GLASSEIDENADER FEINDRÄHTIG VERNICKELT						
GLvn 0,50			2,1	11,5	5,0	791,80
GLvn 0,75			2,3	14,9	7,5	932,80

Silikon- und andere temperaturbeständige Leitungen

Artikel Kurzzeichen	Dimension n x m	Artikelfarbe	Ø mm	Gewicht kg / km	Kupfer kg / km	Preis € / km
GLvn 1,00			2,5	17,6	10,0	1.222,40
GLvn 1,50			2,9	23,6	15,0	1.446,10
GLvn 2,50			3,5	34,5	25,0	1.827,00
GLvn 4,0			4,2	55,3	40,0	3.395,40
GLASSEIDENADER NICKELLITZE						
RNi-GiGi 1,50			3,8	20,0		3.132,60
RNi-GiGi 2,50			4,4	25,0		3.695,50
RNi-GiGi 4,0			5,0	40,0		4.335,50
RNi-GiGi 6,0			5,7	59,0		8.973,80
FEP - MANTELTG TEFLONENERGIELTG UNGESCHIRMT						
LiFL-v6Y6Y 2x0,75			2,2 x 3,8	45,0	15,0	5.337,20
LiV6Y6Y 3x0,75			4,1	60,0	22,5	8.338,30
FEP - MANTELTG TEFLONENERGIELTG GESCHIRMT						
LiV6YCV6Y 2x0,75			5,0	53,0	33,0	6.626,00
LiV6YCV6Y 2x1,50			5,4	45,0	51,0	6.246,40
LiV6YCV6Y 3x1,50			5,7		69,0	7.650,70
PTFE - MANTELLEITUNG, TEFLONLEITUNG						
LE-5Y5Y - J 3x1,0			5,3	75,0	30,0	12.406,30
LE-5Y5Y - J 4x2,5			7,8	162,0	100,0	32.766,60